

AT-NO: JP02001168812A

DOCUMENT-IDENTIFIER: JP 2001168812 A

TITLE: COMMUNICATION CHARACTERISTIC CONTROL METHOD
FOR INDOOR RADIO COMMUNICATION SYSTEM

PUBN-DATE: June 22, 2001

INVENTOR-INFORMATION:

NAME	COUNTRY
MAEDA, YUJI	N/A
TAKATANI, KAZUHIRO	N/A
SHIOKAWA, KANYA	N/A
OSANAGA, AKIHIKO	N/A

INT-CL (IPC): H04B017/00, H04Q007/36

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a communication characteristic control method for indoor radio communication system that can reduce electromagnetic interference caused by a radio wave from a radio base station of other system and an indoor environment, in the case of utilizing the indoor radio communication system such as radio LAN.

SOLUTION: This communication characteristic control method is used for the indoor radio communication system, to control a communication characteristic of a radio communication system consisting of a radio base station and one or more terminal stations that are installed in one indoor place. The communication characteristic control method is characterized, in that a radio wave propagation characteristic between the radio base station placed at a specific position and the terminal station or a radio wave propagation characteristic between a radio station belonging to other radio communication system, and the terminal station is obtained through a simulation or a measurement, one or more communication characteristic control positions, requiring absorption

of the
radio wave in the indoor place are decided on the basis of the
obtained radio
wave propagation characteristic and a barrier having a radio wave
absorbing
function, are placed at the communication characteristic control
positions.

COPYRIGHT: (C)2001,JPO

----- KWIC -----

Abstract Text - FPAR (1):

PROBLEM TO BE SOLVED: To provide a communication characteristic
control
method for indoor radio communication system that can reduce
electromagnetic
interference caused by a radio wave from a radio base station of
other system
and an indoor environment, in the case of utilizing the indoor radio
communication system such as radio LAN.

Abstract Text - FPAR (2):

SOLUTION: This communication characteristic control method is used
for the
indoor radio communication system, to control a communication
characteristic of
a radio communication system consisting of a radio base station and
one or more
terminal stations that are installed in one indoor place. The
communication
characteristic control method is characterized, in that a radio wave
propagation characteristic between the radio base station placed at a
specific
position and the terminal station or a radio wave propagation
characteristic
between a radio station belonging to other radio communication
system, and the
terminal station is obtained through a simulation or a measurement,
one or more
communication characteristic control positions, requiring absorption
of the
radio wave in the indoor place are decided on the basis of the
obtained radio
wave propagation characteristic and a barrier having a radio wave
absorbing
function, are placed at the communication characteristic control
positions.

Application Date - APD (1):
19991208